



ELEVATORI IDRAULICI TRIPLEX *Triplex hydraulic forklifts*

CM 16THAD



**Elevatore idraulico per trattori di media potenza.
Dotato di alzata libera che consente di sollevare il carico senza variare l'ingombro.**

- Cuscinetti radiali a rulli cilindrici
- Quattro catene di sollevamento "Fleyer"
- Profili in acciaio ad "U" ed "H" laminati a caldo
- **Cilindro di sollevamento a doppio effetto**
- Attacco a tre punti cat. 2
- **Alzata libera 200 mm**
- Distributore idraulico a 4 leve
- Traslatore laterale a scorrimento su boccole autolubrificanti
- Forche pieghevoli e regolabili
- Cilindro di brandeggio con snodo regolabile
- Tubi di collegamento al trattore

*Hydraulic forklift suitable to medium power tractors.
Equipped with free lifting for raising the load without changing overall dimensions.*

- Cylindrical roller bearings
- Four "Fleyer" lifting chains
- "U" and "H" shaped hot rolled steel profiles
- **Double effect lifting cylinder**
- Cat.2 three point linkage
- **Free lifting 200 mm**
- Distributor with 4 levers
- Side shift sliding on self lubricating bushes
- Adjustable and pliable forks
- Tilting cylinder with adjustable junction
- Connecting hoses to the tractor



Cuscinetti radiali a rulli cilindrici
Straight roller radial bearings



Catene di sollevamento tipo "Fleyer"
"Fleyer" type lifting chains




Distributore 4 leve
Distributor with 4 levers



Forche pieghevoli e regolabili
Adjustable and pliable forks



Traslatore laterale
Side shift



Alzata libera
Free lifting



Profili in acciaio laminati a caldo
Hot-rolled steel profiles

CM 16THAD				
MODELLO <i>Model</i>	PORTATA <i>Load capacity</i>	ALTEZZA SOLLEVAMENTO <i>Lifting height</i>	INGOMBRO <i>Overall dimensions</i>	PESO <i>Weight</i>
	Kg	mm	mm	Kg
16 THAD 2500	1600	2500	1480	390
16 THAD 3000	1600	3000	1650	445
16 THAD 3200	1600	3200	1730	465
16 THAD 3600	1600	3600	1850	510